



Product Service

Attestation of Conformity

No. N8A 17 11 94747 011

Holder of Certificate: **Xinsu Global Electronic Co., Limited**
Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road
Central
HONG KONG

Product: **Switching power supply unit
(SWITCHING POWER SUPPLY/CHARGER)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 652101711301

Date, 2017-12-07

(Ricky Wang)



CE After preparation of the necessary technical documentation as well as the EU conformity declaration the required CE marking can be affixed on the product. That declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

Page 1 of 3



Attestation of Conformity
No. N8A 17 11 94747 011

Model(s):

XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM,
 XSGxxxxxy, XSGxxxxxyzz, XSExxxxxy, XSExxxxyzz,
 XSECxxxxxy, XSECxxxxyzz
 (xxx=042-730, which denotes the rated output voltage
 from 4.2VDC to 73.0VDC; yyyy=0300-9999, which denotes
 the rated output current from 300mA to 9999mA; zz=EU or
 UK, which denotes for marketing purpose and not affect
 safety, EU=Europe, UK=United Kingdom.)
 XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM,
 XSGxxxxxy, XSGxxxxyzz, XSExxxxxy,
 XSExxxxyzz, XSECxxxxxy, XSECxxxxyzz
 (xxx=042-190, which denotes the rated output voltage from
 4.2VDC to 19.0VDC; yyyy=10000-11000, which denotes
 the rated output current from 10000mA to 11000mA;
 zz=EU or UK, which denotes for marketing purpose and
 not affect safety, EU=Europe, UK=United Kingdom.)

Parameters:

| | |
|------------------------|---|
| Rated Input : | 100-240VAC, 50/60Hz, 3.0A Max. |
| Rated Output : | See page 3 for details |
| Protection Class : | I (For models XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM, XSGxxxxxyMM, XSExxxxxyMM, XSECxxxxxyMM); II (For models XSGxxxxxy, XSGxxxxyzz, XSExxxxxy, XSExxxxyzz, XSECxxxxxy, XSECxxxxyzz, XSGxxxxxy, XSGxxxxyzz, XSExxxxxy, XSExxxxyzz, XSECxxxxxy, XSECxxxxyzz) |
| Degree of Protection : | IP20 |

**Tested
 according to:**

EN 62368-1:2014

Attestation of Conformity
 No. N8A 17 11 94747 011



Product Service

| Model No. | Rated output voltage (VDC) | Rated output current (mA) | Max. rated output power (W) |
|---|----------------------------|---------------------------|-----------------------------|
| XSGxxxxxyMM, XSExxxxxyMM, | 4.2-9.0 | 10000 | 90.0 |
| XSECxxxxxyMM, | 9.1-14.6 | 10000-11000 | 160.6 |
| XSGxxxxxy, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz | 14.7-17.0 | 10000 | 170.0 |
| XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz | 17.1-19.0 | 10000 | 190.0 |
| XSGxxxxxyMM, XSExxxxxyMM, | 4.2-9.0 | 300-9999 | 90.0 |
| XSECxxxxxyMM, | 9.1-14.6 | 300-9999 | 146.0 |
| XSGxxxxxy, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz | 14.7-17.0 | 300-9999 | 170.0 |
| XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz | 17.1-19.0 | 300-9999 | 190.0 |
| XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz | 19.1-22.0 | 300-9500 | 190.0 |
| XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz | 22.1-32.0 | 300-8500 | 205.8 |
| XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz | 32.1-36.5 | 300-6000 | 219.0 |
| XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz | 36.6-57.9 | 300-5000 | 210.0 |
| XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz | 58.0-58.8 | 300-3600 | 210.2 |
| XSGxxxxxyzz, XSExxxxxy, XSExxxxxyzz, XSECxxxxxy, XSECxxxxxyzz | 58.9-73.0 | 300-3400 | 204.0 |